MNHO-081

7th Gen. Intel® i3-7100T 2 LAN ASUS HD Slim Fanless Mini PC

₱ https://www.pondesk.com/product/MNHO-081

Features

- Passively Cooled Dustproof Silent Fanless Mini Desktop
- Ultra-slim Extremelu Flat with a Height of Just 37mm
- 7th Generation Intel® Core™ i3-7100T Kaby Lake Processor
- 3.4GHz, Dual Core, 4 Threads, 3 MB SmartCache
- ASUS Mini ITX Motherboard with 5X Protection II for Dependable Stability
- Dual Display HDMI and DisplayPort •
- Support 4K Ultra HD Disply
- Integrated Intel® HD Graphics 630
- Intel® AES Data Protection
- **Dual Gigabit Ethernet**
- Support up to 32GB SODIMM DDR4 Memory (optional)
- Support M.2 High-Speed Storage •
- 4x USB 3.1 Gen 1 Ports
- Support 802.11 b/g/n/AC WiFi & Bluetooth (optional)
- Multiple Operating System Support Windows & Linux
- Easy Installation & VESA Mount Capability
- Fully Upgradable System
- Energy-saving, Low Power Consumption 18W @ idle
- Ideal for Home, Office, School, Business, Media Center and Education etc.





Specifications

Intel® Core™ Processor i3-7100T 2 Core, 4 Threads 3 MB SmartCache, 3.40 GHz

Memoru

Support up to 32GB SODIMM DDR4 2133/2400MHz non-ECC Memory Two Memory Slot

Storage

Support 1 x M 2 Socket 3 M Keu 2242/2260 Storage

1 x Intel® Gigabit Ethernet I219-V 1 x Realtek® Gigabit Ethernet RTL8111H

Expansion Slots

1 x M.2 Socket with M key, type 2242/2260 (For Storage) 1 x M.2 E key type 2230 (For

I/O Interfaces

2 x Gigabit Ethernet 1 x HDMI 1 x DisplayPort 4 x USB 3.1 Gen 1 Realtek® ALC887 7.1-Channel HD Audio (Mic In & Line Out) DC 12V Input

Graphics

Intel® HD Graphics 630 DisplayPort Resolution Max. 4096 x 2304 @ 60Hz Intel® Quick Sync Video Intel® Clear Video HD Technology Intel® Clear Video Technology

Support Windows 7/8/10 Support Linux

Advanced Technologies

Intel® Huper-Threading Technology Intel® Virtualization Technology (VT-x)
Intel® Virtualization Technology for Directed I/O (VT-d) Intel® VT-x with Extended Page Tables (EPT) Enhanced Intel SpeedStep® Technology Thermal Monitoring Technologies Intel® Identity Protection Technology

Securitu & Reliabilitu Intel® AES New Instructions

Secure Key

Onboard I/O 3 x USB 2.0 Connector

1 x COM Port 2 x SATA 6Gb/s Connector 1x SATA Power Connector 1 x CPU Fan Connector 1 x Chassis Fan Connector 1 x Front Panel Audio Connector 1 x Chassis Intrusion Connector 1 x Clear CMOS Jumper 1 x 2-pin Internal DC Connector 1 x Stereo Speaker Connector

1 x Backlight Inverter Voltage Selection Header

1 x FPD Brightness Header 1 x Panel Voltage Selection Header

1 x Panel off Header 1 x LVDS Connector

1 x DMIC Header

1 x 14-1 pin TPM Connector 1 x System Panel Connector

1 x M.2 Socket 3 with M key, Type 2242/2260 (Support Both SATA & PCIE Mode)

1 x M.2 Socket 1 with E key, Type 2230 (For Wi-Fi/BT, Support PCIE/USB Mode)

Cooling

Completely Fanless Heatpipe Solution Four CPU Copper Heatpipe One Chipset Copper Heatpipe Dual Aluminium Heatsink Blocks Recommended TDP 35W Processor -10°C ~ 30°C Operating Temperature (It is only recommended when

ambient room temperature) Power & Working Environment

adequate air flow location and

the system is placed in a


Adapter Input: AC 100-240V 50-60Hz Adapter Output: DC 12V 5A System Input: DC 12V Consumption: Approx. 18W @ Idle Approx. 28W @ Normal Approx. 40W @ Full Load/Peak Operating Temperature: -10°C ~ 30°C Storage Temperature: -20°C ~ 70°C Humidity: 5% - 95% Non-Condensing

Others

1x VESA Mount

BIOS: AMI Support Hardware Reset Function (L256, 0~255 seconds) Chassis Material: Aluminium Alloy Motherboard: Support Mini ITX (17*17cm) Packagé: 1 x Mini PC 1 x Power Adopter 1 x Cord

Dimensions



308mm x 191mm x 37mm (L*W*H)

Package

MODEL # MNHO-081

- ■1 x Mini PC ■1 x Power Adapter
- 1 x Power Cord
- 1x VFSA Mount

Optional

WiFi & Bluetooth Memory M.2 SSD

80211 AC WiFi (M.2 Module) 4GB/8GB/16GB/32GB DDR4 Memory 64GB/128GB/256GB M.2 SSD





- sales@pondesk.com
- United Kingdom